TECHNICAL SHEET

TUBULAR FRAME SHELVING

CHARACTERISTICS

STRUCTURE

UPRIGHTS	**Materials**: Steel T-shaped uprights 20 x 40 mm **Steel thickness**: 7/10th mm **Pads**: In anti-shear plastic **Paint**: EPOXY powder - painted or galvanised Interlocking parts for easy assembly.

INTERNAL FITTINGS

SHELVES (included and/or optional)	**Materials**: Tubular steel crossbars 300 x 180 mm **Number of crossbars**: 350 mm (2 exterior and 1 interior crossbars), 50 and 70 mm (2 exterior and 2 interior crossbar), **Maximum load per shelf**: Depth 350 mm: W. 1000 - 135 kg / W. 1250 - 85 kg Depth 500 - 700 mm: W. 1000 - 195 kg / W. 1250 - 130 kg Shelves can hold suspension files. **Crossbar adjustment & positioning**: Crossbars adjustable in 25 mm steps. Minimum between 2 crossbars: 75 mm.
Hardboard shelf top (optional)	**Materials**: Hardboard **Thickness**: 2 mm **Other**: Available for all dimensions

Height (in mm)	2000	2250	2500
Number of crossbars	5	6	7

OVERALL & USEFUL DIMENSIONS (in mm)

SHELVING

H. 2000

	Starter unit						Add-on					
Width	1040			1290			1010			1260		
Depth	350	500	700	350	500	700	350	500	700	350	500	700

H. 2250

	Starter unit						Add-on					
Width	1040			1290			1010			1260		
Depth	350	500	700	350	500	700	350	500	700	350	500	700

H. 2500

	Starter unit						Add-on					
Width	1040			1290			1010			1260		
Depth	350	500	700	350	500	700	350	500	700	350	500	700

CROSSBARS

	L. 1000	
	Starter unit	Add-on
Overall width between uprights	1040	1010
Useful width between uprights	960	

	L. 1250	
	Starter unit	Add-on
Overall width between uprights	1290	1260
Useful width between uprights	1210	

Made in France

5 YEARS GUARANTEE

40% RECYCLED MATERIALS

FULLY RECYCLABLE