


ATTITUD

FEATURES



OFFICE CHAIR

BACKREST	<p>Fabric backrest (with headrest)</p> <ul style="list-style-type: none"> Shaped plywood internal structure, polypropylene shell / Injection moulded PU foam 22 mm thick, 55 kg/m3 Foam glued to the internal structure, no fabric adhesive bonding Padding effect realised with staples <p> Height adjustment via rack-and-pinion (+ 60 mm), reverse lock safety mechanism</p> <p>Padded backrest</p> <ul style="list-style-type: none"> Polyamide frame padded with Kingflex fabric from Fidivi (100% Polyester Trevira CS / foam 6.5 mm thick, density 24 kg/m3) Padding affixed directly to the backrest structure <p> Height adjustment via rack-and-pinion (+ 60 mm), reverse lock safety mechanism</p>
CONNECTOR ROD	<ul style="list-style-type: none"> Steel rod 6 mm thick, no housing sheath Rod secured directly to the backrest and mechanism using screws
SEAT	<ul style="list-style-type: none"> Polyamide internal structure, polypropylene shell / injection moulded foam, CMHR35E 60 mm thick, 35 kg/m3 Padding effect realised with staples <p> Adjustments: optional adjustable seat with 6 preset positions, spaced at 11 mm intervals with an overall range of 55 mm</p> <p> Easily interchangeable seat</p> <ul style="list-style-type: none">> Secured by 4 screws for the version without armrests> Secured by 10 screws for the version with armrests
ARMRESTS	<p>4D Armrests</p> <ul style="list-style-type: none"> Polyamide with flexible polyurethane (PU) armrest sleeve 4 adjustment possibilities> Width: 30 mm range of adjustment on each side> Height: 11 positions spaced at 10 mm intervals with an overall range of 100 mm> Depth: 5 positions spaced at 12.5 mm intervals with an overall range of 65 mm without notches> Rotation: 3 positions spaced at 10° intervals with an overall range of 25° without notches
MECHANISM & ADJUSTMENT SYSTEM	<p>Ergonomic Synchro Mechanism</p> <ul style="list-style-type: none">> Synchronised seat and backrest inclination through 15°> Backrest locking to 4 preset positions> Backrest tension adjustment performed using a hand lever located to the side of the seat
LEGS	<p>5-point star base in black finish, as standard</p> <ul style="list-style-type: none"> Black polyamide ø 700 mm Gas lift mechanism, black finish, adjustment range of 125 mm <p>5-point star base in chrome finish, optional</p> <ul style="list-style-type: none"> Chromed aluminium ø 700 mm Gas lift mechanism, black finish, adjustment range of 125 mm <p>Castors</p> <ul style="list-style-type: none">> Hard-floor castors Ø 50 mm (polypropylene castor housing and wheel, non-marking thermoplastic rubber banding)> Soft-floor castors Ø 50 mm (polypropylene castor housing and wheel)

	OFFICE CHAIR WITH HEADREST	
	<div></div> <div>Fabric high back</div>	
OVERALL DIMENSIONS (in mm)		
Width	666	
Depth	634	
Height	1290	
USEFUL DIMENSIONS (in mm)		
Seat height	440 / 565	
Width x Seat depth	520 x 460	
Backrest height (Distance between top of backrest/top of seat)	665 / 725	
Height 4D armrests (Seating distance/top of armrest)	170/270	
WEIGHT (kg)		
Net weight	16,56	
Max. weight 1D armrests	40	
Max. weight 4D armrests	40	
Max. load	120	