

# TECHNICAL SPECIFICATIONS SHEET

## 24H PRO

### FEATURES



SEAT AND BACKREST	<p>Reinforced beech plywood internal structure (THK 13 mm) / high density foam THK 60 mm, 40 Kg/m3</p> <p>Covering: Fabric 24/7+ hard wearing:                  &gt; Resistance to abrasion: 550,000 Martindale cycles                  &gt; Fire-resistance rating EN 1021.1 and 2</p> <p>Black finish</p> <p>Reinforced: gas lift, seat/backrest join, screws and castors</p>
ARMRESTS	<p><b>Fixed armrests</b>                  Chrome tube with fabric armrest sleeves</p>
MECHANISM & ADJUSTMENT SYSTEM	<p>Forward axis tilt mechanism                  &gt; Backrest locking to 6 preset positions                  &gt; Backrest tension adjustment handwheel located at the front of the seat</p>
BASE	<p><b>5-point star base</b>                  Die-cast polished aluminium, ø 725mm                  Pneumatic hydraulic gas lift mechanism in a black finish, adjustment range of 950 mm</p> <p><b>Castors</b>                  As standard: self-braking castors ø 50 mm, for soft and hard floors (polypropylene castor housing and wheel)</p>



**TASK CHAIR**



**OVERALL DIMENSIONS (in mm)**

Width	ø 725
Depth	ø 725
Height	1,195 / 1,290

**USEFUL DIMENSIONS (in mm)**

Seat height	460 / 555
Width x Seat depth	510 x 540
Backrest height (Distance between top of backrest/top of seat)	710
Height of Fixed Armrests	240 mm

**WEIGHT (kg)**

Max. load	160
-----------	-----

