







GUEST



PROPERTIES

<p>GENERAL</p>	<p>Melamine-covered particle boards, thickness 38 mm or 19 mm. 2 faces treated with anti-reflective hue Density of panels 650kg/m³ Flat edges with ABS stuck on thickness 2mm, chamfered top and bottom. Edges matched to the worktop hue Boards originating from sustainably-managed forests (PEFC). Fire classification M3 (average flammable combustible) in accordance with standard NF EN 13501-1 Boards certified E1 (control of formaldehyde emissions) with 6.5mg HCNO/ 100 mg and compliant with standard NF EN 717-2.</p> <p>Melamine boards (except for Brunswick oak hue R3 and coffee oak M9) compliant with standard ISO22196 which give them anti-bacterial properties.</p>
<p>WORKTOPS AND UPPER SHELVES</p>	<p>Worktops 38 mm thick</p> <p>Standard worktops fitted with 1 or 2 cable ports ø 80 mm (except DDA model) There are also W120 and W160 worktops with a scalloped edge for positioning of a screen (up to 22 inches) onto a metal shelf under the work surface. These worktops are pre-drilled for ø 80 mm cable ports at 2 ends.</p>
<p>LEGS</p>	<p>Melamine boards thickness 38 mm.</p> <p>Short legs (D. 430 mm) to facilitate circulation between 2 modules or long legs (D. 800 mm) to close a configuration Legs fitted with adjustment stabilisers (travel 15 mm)</p> <p>Finishes: Snow white</p> 
<p>MODESTY PANEL</p>	<p>Structural melamine modesty panels thickness 19 mm on which are fastened melamine or metal cladding.</p> <p>Finishes: Snow white</p>
<p>MELAMINE CLADDING</p> 	<p>Melamine board thickness 19 mm. Is fastened on modesty panels by woodscrews</p> <p>Finishes: see shade card on range sheet or catalogue</p>
<p>METAL CLADDING</p> 	<p>Is fastened on modesty panels by inserts and screws 2 facing boards for low modules, 3 boards for high modules</p> <p>Metal sheet thickness 0.7 mm, laser perforated 3 choices of finish:</p> <ul style="list-style-type: none"> - dot - leaf - slant 

OPTIONS




<p>OVER-SHELF</p> 	<p>W.1000 x D. 376 x H. 277 mm</p> <p>There are the versions:</p> <ul style="list-style-type: none"> > Neutral without inscription > With a laser-cut inscription: <ul style="list-style-type: none"> - "welcome" - "bienvenue" - personalised (for example, company logo): consult us <p>> Finishes: see shade card on range sheet or catalogue</p>
<p>LED KIT</p> 	<p>LED kit for over-shelf: W. 950 mm</p> <p>Fastening by double side in the low and/or back inscription</p> <p>There is a UK version with adaptor</p> <p>White LED kit:</p> <ul style="list-style-type: none"> > White light > Switch on user side <p>Colour LED kit:</p> <ul style="list-style-type: none"> > Colour lights are either fixed or changing > Operates with remote control
<p>POWER & CABLE MANAGEMENT</p>	<p>See corresponding Technical Data Sheets for details.</p>
<p>CABLE TROUGH</p>	<ul style="list-style-type: none"> > Sheet steel thickness 0.7 mm > Fastened by 2 woodscrews > W. 900 x H. 100 mm > Finishes: white SO or aluminium SA

DIMENSIONS

High standard modules	 RECTANGULAR	 LEFT OR RIGHT ANGLES (*)
-----------------------	--	---

OVERALL DIMENSIONS (in mm)			
	Without scalloped edge	With scalloped edge	
Depth	840		840
Width	800 / 1200 / 1600	1200 / 1600	840
Desk height	740		740
Total height	1130		1130

USEFUL DIMENSIONS (in mm)			
Depth	800		800
Height of work surface / counter top unit	352	461	350

Low modules	 DDA For end (L or R)	 DDA For middle or end (L or R)	 Standard For middle or end (L or R)
-------------	---	---	--

DIMENSIONS (in mm)			
Depth	1150	1150	840
Width	1250	1000	
Desk height	740		

* Descriptions of left and right-hand side are determined in relation to the position of the user (behind the bench).