

TECHNICAL SPECIFICATIONS SHEET

ECONOMY FILING CABINETS

FEATURES



SHELL

SIDES BACK BASE TOP	Construction: Welded one-piece construction structure from a single sheet of steel. Sheet steel thickness: shell 6/10th mm, top and base 8/10th mm. Manufacturing process: Manufactured using 40% recycled steel and is 99% recyclable. Guarantee: 2 years Other: Drilled openings located on the back and sides, to join units or secure to wall.
------------------------------	---

OPENING MECHANISM

DRAWER	Construction: Welded one-piece construction structure from a single sheet of steel. Thickness: Drawers 5/10th. Handle: Black plastic with built-in label holders. Lock: Numbered lock with 2 keys (1 lock for both drawers) Runners: Ball-bearing runners, 80% drawer depth extraction - anti-tipping safety system and selective drawer opening mechanism. SF capacity (per drawer): +/- 35 A4 SF files with V-shaped spines Max. load (per drawer) : 30 kg Other: Drawers with plain solid sides and base panels to receive all types of documents.
--------	--

USABLE DIMENSIONS & WEIGHT OF CREDENZAS

A4 FILING DRAWERS	 2 DRAWERS	 4 DRAWERS
OVERALL DIMENSIONS (in mm)		
Height	711	1282
Width	413	413
Depth	400	400
USABLE DIMENSIONS (in mm)*		
Height	255	255
Width	335	335
Depth	330	330
WEIGHT (kg)		
Empty	22	39
Max. load per drawer	35	35

* per drawer
Carbon footprint for standard credenza: 60 to 110 kg eqCO2

