


CHARACTERISTICS



WORKTOPS

MELAMINE	<p>> Melamine covered particle board panels, 38 mm or 25 mm thick. 2 sides treated with an anti-reflective coating Panel density 650kg/m3 Bonded ABS edge banding, 2 mm thick, rounded on upper and lower edges. Edge banding to match worktop finish</p> <p>Panels sourced from sustainably managed forests (PEFC). Fire rating M3 (combustible, moderately flammable) in accordance with the standard NF EN 13501-1 Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and compliant with standard NF EN 717-2 Melamine panels (except Brunswick oak R3 and Coffee oak M9) comply with the standard ISO 22196 for antibacterial properties.</p> <p>> Some worktops are pre-cut for top-access housings (to be ordered separately; see Options below) Metal cable trough included. > Circular worktops ø 1000 and 1200 are ready-drilled for cable ports (to be ordered separately; see Options below)</p>
LAMINATE	<p>> Laminate covered particle board panels, 25 mm thick. 2 sides treated with an anti-reflective coating Panel density 650kg/m3 Bonded ABS edge banding, 2 mm thick, rounded on upper and lower edges. Edge banding to match worktop finish "Sanitized" antibacterial laminate: 99.9% of bacteria destroyed in 24 hours. Resistant to abrasion, shocks, humidity, heat, stains and scratches.</p> <p>Panels sourced from sustainably managed forests (PEFC). Fire rating M3 (combustible, moderately flammable) in accordance with the standard NF EN 13501-1 Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and compliant with standard NF EN 717-2</p>


LEGS AND STRUCTURE

<p>CENTRAL METAL STEM OR 4 LEGS</p> 	<p>> Central circular section stem in tubular steel ø 89 mm (leg with cable management - see below), base plate ø 710 mm</p> <p>> Central square section stem 60 x 60 mm, base plate: 500 x 500 mm</p> <p>> 4 circular section legs in tubular steel ø 60 mm</p> <p>> 4 square section legs in tubular steel 60 x 60 mm</p> <p>ABS adjustable stabiliser for 4-leg version. Adjustment through 20 mm. Upper plate in sheet steel with brace</p>
--	---








<p>CIRCULAR CENTRAL STEM WITH CABLE MANAGEMENT</p> 	<p>Worktop leg pre-drilled for cable port Allows the passage of the cables through the shaft of the leg and under the slightly raised base plate. Compatible with cable ports for diameter ø 80 mm ref 6478163 + fin, ref 6478140/142 + fin, and ref 6478144 + fin.</p> <p>Not compatible with retractable cable port housings</p>
<p>MELAMINE PANEL LEG</p> 	<p>> Melamine panel leg 38 mm thick, matching worktop Assembly on metal inserts Legs with adjustable stabilisers, adjustment through 15 mm.</p> <p>For the H 748 mm version, structural melamine modesty board For the H. 1050 mm version, metal structural footrest bar, tubular section 50 x 50 mm</p>



POWER & CABLE MANAGEMENT OPTIONS

<p>WORKTOP CABLE MANAGEMENT</p> 	<p>Plain cable ports</p> <p>Cable ports for direct connectivity</p> <p>Cable ports with retractable covers for direct connectivity</p> <p>Cable ports with induction chargers</p> <p>One-way or dual hinged top-access modules, with or without a socket feed</p> <p>See corresponding technical sheets</p>
---	---



EXTERNAL DIMENSIONS (in mm)				
CIRCULAR WORKTOPS				
Depth/width	ø 600	ø 800	ø 1000	ø 1200
Leg height	1045	735	735	735 / 748
Worktop predrilled for cable port ø 80	no	no	yes	yes
Worktop type	Lam. + mel. 25 mm	Lam. + mel. 25 mm	Lam. + mel. 25 mm	Lam. 25 mm + mel. 25/38 mm
Leg type	1 central circular section	1 central circular section	1 central + 4 circular section legs	1 central + 4 circular section legs

BARREL-SHAPED WORKTOPS		
Depth	2000	2200
Width	1000	1100
Leg height	735	748
Worktop predrilled for cable port ø 80	no	no
Worktop pre-cut for top-access housing	yes	yes
Worktop type	mel. 25 mm	mel. 38 mm
Leg type	2 central + 4 circular section legs	2 central + 4 circular section legs

SQUARE WORKTOPS		
Depth	800	1200
Width	800	1200
Leg height	735 / 1060	748
Worktop predrilled for cable port ø 80	no	yes
Worktop pre-cut for top-access housing	no	yes
Worktop type	Lam. + mel. 25 mm	mel. 25 mm
Leg type	1 central square section	4 square section legs

**Made
in France**

