CHATBOX by SILEN

PROPERTIES

	> Supply cable of 3 metres with Eur, UK or CH socket			
POWER AND CABLE MANAGEMENT	 Cabins equipped as standard with Eur, UK or CH sockets: CB1: 1 socket + 1 USB-C (on the wall) CB2: 1 socket + 1 USB-A + 1 USB-C (centred on the back wall) CB4: 1 socket + 2 USB-A (on the side wall) 			
VENTILATION	more than 22l/s (79m3/h)	more than 55I/s (198m3/h)	more than 85I/s (306m3/h)	
	CB1	CB2	CB4	
	Air circulation			
	3.4w	5.1w	10.2w	
	CB1	CB2	CB4	
	Max consumption			
	> Low consumption air circulation system > Very good air circulation			
	6.7w, 4000k, 900lm	28w, 4000k, 2240lm	56w, 4000k, 4480lm	
LIGHTING	CB1	CB2	CB4	
	> Low consumption LED with presence detector			
ACOUSTIC	34 Db (measured on site acco	rding to standard ISO 16283-1	_)	
	7	10	20	
BASE	CB1	CB2	CB4	
	Number of adjustable stabiliser feet			
	> <u>Adjustable stabiliser feet</u> : For levelling - Adjustable from the inside			
INTERIOR	> Cabin CB1 is equipped as standard with a white laminated anti-bacterial worktop H1050xL700xP300 mm, 132mm thick			
	> <u>Wall</u> and ceiling Echofree recycled acoustic panels > <u>Floor</u> : Antistatic, stain-resistant fitted carpet for public spaces (standard EN 1307)			
EXTERIOR	 <u>Glazed walls</u>: Sécurit acoustic transparent glass <u>Doors</u>: Left or right opening (can be changed after installation), magnetic closure <u>Side panels</u>: black or white metal (other colours possible, consult us) 			
	> Glazed walls: Sécurit acquet	ic transnarent glass		
GENERAL	- CB4: up to 6 persons They are sold empty or equipped with a table (for versions CB2 and CB4) to be ordered with the cabin.			
	- CB2: up to 4 persons			
	- CB1: 1 person standing	nat can accommodate 1 - 6 per	SUHS.	





OPTIONS

Table	
	To be ordered at the same time as the cabin > Laminated board 21 mm thick - white anti-bacterial > Black metal feet > Central on fixed feet, for CB2 or CB4 cabins Dimensions: H.730 x W500/1400 x D716 mm > Side on electrically-adjustable feet for CB2 cabin Dimensions: H.700/1100 x W900 x D550
Screen support arm without articulation	To be ordered at the same time as the cabin
235/9.2 2007/9 1003.9 1003.9 VESA mounting holes	For cabins CB1, CB2 or CB4 (to be ordered at the same time as the cabin) > To support screens from 19 to 43 inches > Vesa 75, 100 and 200 > distance between the wall and the screen: 2.3 cm > Maximum weight supported 20 kg > Finish: matt black
Benches	> Dimensions: Backrest height: 770 mm - Seat height: 460 mm - Depth: 620 mm - Width: 900 mm > Black metal feet. > Seat and backrest of fire-resistant Nevotex fabric (dark grey colour, other colours with supplement, please ask)
Other	The cabin can be integrated with other products from the EOL range > Eloise Tables > Zelie Writing Table > Task Chairs > Bip Easy Chairs > Tom, Spoon Stool etc.





2

DIMENSIONS

CABINS (in mm)					
	CB1	CB2	CB4		
HxWxD Exteriors	2220x1000x1000	2220x2130x1030	2220x2130x1940		
M2 to the floor	1,00	2,19	4,13		
HxWxD Interiors	2040x870x980	2040x2000x930	2040x2000x1860		
Back wall	Glazed	Glazed	Glazed		
Number of persons	1	up to 4	up to 6		
Weight (kg)	370	550	980		
Power and cable management	1 socket + 1 USB-A	2 socket + 2USB-A	1 socket + 2USB-A		

EQUIPMENT (in mm)					
Tables					
Tables	For CB2 (central)	For CB4 (central)	For CB2 (side)		
Height	730	, ,	700 / 1100		
Width	500	1400	900		
Depth	716		550		
Benches					
Height	770				
Width	900				
Depth	620,00				
Seat height	460				
Seat depth	450				
Weight supported (kg)	200				





3